

# 1ST FEBRUARY - 30TH APRIL 2025

# DIESEL REFUELLING ESSENTIALS

## 51039

# ALEMLUBE 1" AUTO SHUT OFF DIESEL NOZZLE

- Delivery rates of up to 120L/min
- Automatically cuts off when a diesel tank is full
- 1"BSP swivel included
- Maximum working pressure of 80psi (5.5 bar) (not suitable for gravity feed applications)
- Suitable for applications involving an electric diesel transfer pump only
- Body: aluminium.
   Seals: buna-n & viton
- Outlet spout: aluminium with viton cased oil seal
- Weight 1.6kg



## 51039M

## ALEMLUBE AUTO SHUT OFF DIESEL FUEL NOZZLE WITH BUILT-IN METER

- Automatically shuts off on back pressure
- Digital meter with 5-digit current dispensed total resettable
- Digital meter with 7-digit cumulative total
- non resettable
- Flow rates of up to 120L/min
- Operating pressures of up to 50psi (3.5 bar)
  Operating temperature
- range: -25°C to 55°C
- 1" BSP(f) swivel inlet & 24mm (1") outlet spout
- Accurate to ±1%
- Suitable for dispensing diesel fuel



## **ALEMLUBE**

# PORTABLE & LOCKABLE DIESEL REFUELLING STORAGE AND DISPENSING PODS

· Australian made, heavy duty, robustly constructed polyethylene tank

· Lockable lid aids fuel & dispensing kit security

 Dispensing kit consists of a 12V pump, antistatic fuel delivery hose, 2 meter battery cables & auto shut off nozzle

· Storage & dispensing of diesel fuel only

· Forklift lift points & tie down capability

· Built in nozzle holster



0
0
0
0
0











# HOSE, CABLE & BARRIER REELS AND GREASING EQUIPMENT

### AR1225GWG

## **REWINDA**

## **GARDEN HOSE REEL - 25M X 12MM ID**

- Supplied with 25m x 12mm ID PVC garden hose & lead in hose
- Impact resistant UV stabilised covers for maximum durability
- Quick connector outlet hose with nozzle
- Detachable steel mounting bracket enables 180° hose reel rotation
- Working pressure: 150 psi (10 bar)
- Inlet: 3/4" BSP(f)



## **AR1217HWR**

## **REWINDA**

## **HOT WATER HOSE REEL - 17M X 12MM ID**

- 17m x 12mm ID ethylene propylene diene monomer hose & 0.9m feed in hose
- 3/4" BSP(f) inlet hose / 1/2"BSPT(m) outlet hose
- Constant speed control ensures safe & accurate rewinding
- Impact resistant UV stabilised polypropylene covers
- Working pressure of up to 300psi (20bar)
- Working temperature -40°C to +90°C





## AR1020HPWR

## **REWINDA**

## HIGH PRESSURE WASHDOWN HOSE REEL

GREAT VALUE!

- 20M X 10MM ID
- The speed rewind control system on all models ensures that the hose retracts at a safe & steady speed
- The stop-at-any-point latching mechanism secures the hose at the desired length every time





## AR1020CAB

## REWINDA

## **COMPRESSED AIR HOSE REEL - 20M X 10MM ID**

- Gen3 hybrid polymer hose
- High grade Impact resistant UV stabilised cover
- 20m x 10mm ID hose & 0.9m lead-in hose
- 3/8" BSPT(m) inlet/outlet connections
- Dimensions of 580mm (L) x 480mm (H) x 270mm (W)

# Also available: AR1020CAR

Air Hose Reel 20m x 10mm ID **\$449.00** 





## A14512

## ALEMLUBE QUICK RELEASE GREASE GUN COUPLER - 1/8" BSP(F)

- Works with all grease gun types
   pneumatic, manual & battery
- 1/8" BSPT(f) thread
- Maximum working pressure of 10,000psi (690bar)
- Fits all metric & SAE specification grease nipples
- 4 hardened spring steel jaws resilient under high pressure
- Suitable for high pressure, heavy duty greasing applications
- 90mm in length

## Also available:

## A14511

Quick Release Grease Gun Coupler - 1/8" NPT(f)

\$39.95



## 600A


## ALEMLUBE 450G LEVER ACTION GREASE GUN

- Grease pressures of up to 12,000psi (828bar)
- Delivers up to 1.6g of grease per stroke
- Bulk filling capacity of 500g
- Ever-Flow System enables the gun to be used with thick/tacky greases up to NLGI2
- Light weight aluminium die cast head assembly
- High pressure high volume option
- Manufactured in Germany



## ALEMLUBE 20V LITHIUM-ION CORDLESS GREASE GUN

- Grease pressures up to 7,250psi (500bar)
- Adjustable delivery rates of 100g/min or 160g/min
- Able to dispense up to 16 cartridges before battery recharge is required
- Backlit display provides real time battery level, grease level
   grease dispensed operator feedback information



Battery recharge time of 70 minutes



\$799.00 GREAT VALUE!





### AR1024020CRR

## **REWINDA**

## 240V ELECTRIC CABLE REEL - 10AMP

- 240V, maximum 10amp
- Supplied with 20m of 3G x 1.5mm<sup>2</sup> cable
- Maximum power when coiled is 1,600W when uncoiled 3,200W





## AR1524020CRR

## **REWINDA 240V ELECTRIC CABLE REEL - 15AMP**

- 240V, maximum 15amp
- Supplied with 20m of 3G x 1.5mm<sup>2</sup> cable
- Maximum power when coiled is 1,600W when uncoiled 3,200W







## AR30DBRR

## **REWINDA** DANGER SAFETY BARRIER REEL

- Provides a temporary barrier to clearly identify dangerous areas in the workplace or public spaces
- Supplied with 30m x 48mm of red/white band with fixed-handle
- Integral swivelling steel wall bracket
- Automatic spring rewind mechanism





10 YEAR

#### AR30CBRR

## **REWINDA CAUTION SAFETY BARRIER REEL**

- Provides a temporary barrier to clearly identify dangerous areas in the workplace or public spaces
- Supplied with 30m x 48mm of yellow/black band with fixed-handle
- · Automatic & positive latching mechanism with speed control break system





## 680AN

## ALEMLUBE **450G AIR OPERATED GREASE GUN**

- Develops grease pressures of up to 3,290psi (226bar)
- Pressure ratio of 40:1
- Delivers up to 182g per minute
- Recommended maximum air pressure of up to 98psi (6bar)
- Suitable for use with grease up to NLGI2
- Flexible extension length of 50cm
- Suits 450g cartridge or bulk grease
- Continuous flow or single shot operation



## 660AN

## **ALEMLUBE 450G TRIGGER ACTION GREASE GUN**

- Grease pressures of up to 8,500psi (586bar)
- Delivers up to 1.1g of grease per stroke
- Twin Lock System seals the piston & eliminates the possibility of dummy lubrication
- Ever-Flow System enables the gun to be used with thick tacky greases up to NLGI2
- Manufactured in Germany



## L4676

## **ALEMLUBE METRIC GREASE NIPPLE ASSORTMENT KIT**

- Includes 100 of your most popular automotive type grease nipples in a convenient compartmentalised refillable carry kit
- All grease nipples included are case hardened, fully chromated, zinc passivated, batch tested to 8,000psi (552bar) & conform to international standards including BSS 1486, DIN 71412, SAE J534 and JIS B1575

## Also available:

## 1 4675

101 Industrial grease nipple assortment kit \$100.10





# **CAPITAL & GENERAL WORKSHOP EQUIPMENT**

### **RAV4501L**

### **RAVAGLIOLI**

## 5.0T ELECTRO-HYDRAULIC 4-POST VEHICLE HOIST

- Long 5,700mm platform with adjustable width
- Automatic mechanical backup safety devices with pneumatic release
- Automatic anti toe trap alarm during final stages of lift descent

9.399.00 GREAT VALUE



AA50CF2P

## **ALEMLUBE AUTOMOTIVE 5.0t ELECTRO-HYDRAULIC CLEAR FLOOR HOIST**

- · Load capacity of 5,000kg
- · Lifting height 1,800mm
- Minimum pad height 110mm
- Post height 4,420mm
- Ideal for light commercial vehicles
- Includes 4WD extension





20044

## **ALEMLUBE FOLDABLE LED SLIM & COMPACT WORK LIGHT**

- Light Source: High power COB LED Main light High power SMD LED - Top light
- Luminous Power: 120 lumen to 800 lumen
- Operating time: 2.5 hours to 9 hours
- · Battery Specification: Li-Ion 3.7V, 2600mAh, 9.62Wh
- · Charging Time: 4 hours
- · Charging: USB-C 1m charging cable
- Operating temperature:

 $-10^{\circ}$ C to  $+40^{\circ}$ C



#### 20099

## **ALEMLUBE** RECHARGEABLE LED HEAD LAMP

- · Light Source: High power COB LED
- Luminous Power: 100 lumen to 300 lumen
- Operating time: 2 hours to 5.5 hours
- Battery Specification: Li-Po 3.7 V, 1500 mAh, 5.55Wh
- Operating temperature: -10°C to +40°C
- · Charging: USB-C 1m charging cable
- · Charging Time: 2.5 hours





## 66034

## **ALEMLUBE** 1.5L BRAKE CLEANER SPRAYER

- · Large filling opening
- Safety valve at 36psi (2.5bar) with depressurisation option
- · Easy tool-free maintenance
- Strong translucent bottle with level indicator
- · Not suitable for use with acids
- 1.5L capacity





## 7701A

## MALEMLUBE **1L MULTI PURPOSE TOP UP KIT**

- Ideal for topping up difficult to access oiling points in the workshop & at home
- Suitable for all oils, automatic transmission fluids, brake fluids & some hand cleaners
- · Not suitable for combustible fluids
- Self-contained unit prevents oil contamination when not in use
- 1L capacity





## 5000MFN

## **ALEMLUBE 5L MULTI PURPOSE OIL MEASURE**

- 5L polyethylene oil measure will not dent, scratch or corrode
- Flexible delivery spout makes the topping up of engines, gear boxes, diffs, transmissions & crank cases a quick and easy proposition

## Also available:

2000MFN

2L Oil Measure \$38.00



## 001014-25

## **ALEMLUBE**

## **ICAN 5L OIL CONTAINER WITH 25MM POUR LID KIT**

- Fully sealed system reduces the chance of lubricant contamination
- · Quick fill port for safe contaminant free refills
- On/off toggle switch for easy dispensing
- Threaded port with optional desiccant filter for added protection





## **KPH350.45**

## **RAVAGLIOLI ELECTRO-HYDRAULIC VEHICLE HOIST**

- Capacity: 4,500 kg
- Maximum lifting height: 1,863mm (1,928mm with extensions)
- · Lifting time: 54 secs
- Minimum pad height: 100 mm





## AAPMC85T

**ALEMLUBE AUTOMOTIVE PREMIUM HEAVY DUTY MOBILE WIRELESS COLUMN LIFTS** - 8.5t PER COLUMN

• Lifting capacity 8.5t per column

- Wireless connection
- Maximum lifting height 1,700mm
- Each column can be a master or a slave
- Up to 16 columns in a system
- Cable free design, with built-in double batteries



#### **AAP8887**

## ALEMLUBE AUTOMOTIVE PREMIUM **5M HEAVY DUTY WORKBENCH/STORAGE UNIT**

• Includes: 2m single door storage cabinet, 5 drawer base cabinet, 4 drawer base cabinet, 2 door base cabinet, rubbish bin cabinet, 5 drawer roller cabinet, 2m double door cabinet, 5 x overhead cabinets, 5 x pegboards modules, 3.4m stainless steel bench top with MDF, 2 x power boards & LED lighting





## Also available:

**AAP8883** 

2.3m heavy duty workbench/storage unit \$3,899.00

## **AAP8884B**

3m heavy duty workbench/storage unit \$5,099.00

## AAPWB220V

## **ALEMLUBE AUTOMOTIVE PREMIUM MEGASPIN COMPACT DIGITAL**

- VIDEO WHEEL BALANCER
- Rim width setting range: 1.5" to 20" · Rim diameter setting range: 10" to 30"
- Single-phase power supply 230V, 50Hz
- Balancing speed: 100rpm
- Measuring cycle for 15kg wheel: 4.7 seconds

 Software programs Virtual Sonar & Laser Line

 Maximum wheel weight: 75kg







- Large 24" LCD screen is easy to read & analyse
- Bluetooth transmission between the front heads and the cabinet
- 90,000 vehicle database
- · No runout required when using STDA95E Quick Clamps

 Full customer database



## AAPKA24

## **ALEMLUBE AUTOMOTIVE PREMIUM MOBILE EVAPORATIVE AIR COOLER**

- 240V/50HZ 650W 3 speed motor
- Fan diameter: 24"/60cm
- · Maximum cooling area: 150sqm
- Tank capacity: 70L
- Maximum water consumption: 10L/H
- Dimensions:
  - 92.5cm x 58cm x 144cm

## Also available:

## AAPKA30

Alemlube Automotive Premium Mobile Evaporative Air Cooler

\$1,500.00







# DIESEL REFUELLING & OIL EQUIPMENT

### 52000

## ALEMLUBE 12V DIESEL REFUELLING TANK KIT

• Capable of flow rates of up to 50L/min

 Includes 4m of antistatic fuel delivery hose, 2m of battery cable, a stainless steel & brass fuel filter and a manual nozzle

 Maximum head capacity of 15m

 Suction capacity of up to 2m





## 52050

### **PIUSI**

## 12V DIESEL FUEL TRANSFER PUMP

- Flow rates of up to 50L/min
- Self-priming 12V electric pump with on/off switch

 Maximum working pressure of 22psi (1.5 bar)

- 3/4" BSP(f) inlet & outlet connections
- Watts: 300
- RPM: 2,900
- Amps: 24

\$**559**.00



## 504250

#### **SAMOA**

## **SPRING REWIND OIL HOSE REEL**

- Maximum working pressure of 2,300psi (160bar)
- 1/2" BSP(m) inlet & outlet threads
- Supplied complete with 15m x 1/2" ID R1 hose & 0.8m inlet hose
- Full 1/2" ID port, shaft & swivel
- Heavy duty double pedestal construction
- Floor, wall, ceiling or tank mountable



#### 505224N

#### **SAMOA**

## 15M X 19MM ID SPRING REWIND HOSE REEL

- · Heavy duty full metal double pedestal construction
- Hose capacity: 15m x 19mm ID
- Hose pressure rating 1,520psi (103bar)
- 3/4" BSP(f) inlet/outlet thread
- True 3/4" full flow shaft & ports
- Manufactured using 4mm gauge steel





## 52004A

## PIUSI 12V HIGH VOLUME DIESEL DRUM PUMP WITH AUTO SHUT-OFF NOZZLE

- 1" BSP(f) inlet/outlet
- Flow rates of up to 85L/min
- Telescopic down tube suits fuel tanks up to 1,000mm deep
- Includes an automatic shut off nozzle
- Self priming vane pump with sintered steel rotor & acetyl resin vanes
- Total maximum discharge lift capacity of 10m
- Dry prime of 2m

## Also available: 52004

12V High Volume Manual Diesel Pump 85L/min \$1,358.00





## 030050

## EL SERIES

## **OIL TRANSFER KIT WITH METER**

- Flow rates of up to 10L/min
- Includes a 3:1 ratio oil pump,
   1/2" hydraulic hose, electronic oil meter & adjustable
   2" bung adaptor
- Suits 205L drums & transfers engine, gear hydraulic oils up to SAE130 and ATF
- Air consumption of 3.6 cfm at 150psi
- Maximum operating pressure of 450psi (30bar)
- Maximum oil viscosity of SAE130
- Oil control valve with meter



## 10028

## ALEMLUBE HEAVY DUTY 20L GEAR OIL DRUM PUMP

- Heavy duty fully serviceable drum pump delivers 170mL on the downstroke
- Non-drip nozzle
   & drain back holster
- Height adjustable bung adaptor & two extra adaptors to suit local and international 20L drums supplied standard
- Ideal for use with engine, hydraulic, gear, diff & synthetic oils







### 52004-3AC

## **PIUSI**

### 12V HIGH FLOW DIESEL TRANSFER PUMP

- Flow rates of up to 85L/min
- Powerful self-priming, rotary vane, positive displacement bi-pump
- 1" BSP(f) flanged connections
- Duty cycle of 30 minutes on / 30 minutes off





### 424170

### SAMOA

### **20KG GREASE KIT WITH CARRY HANDLE**

- Delivery rates of up to 0.9kg/min
- 55:1 ratio air motor develops grease pressures of up to 7,950psi (548bar)
- · Handles high density, tacky greases up to NLGI2
- Supplied complete with a 4m long hose assembly

## Also available: 424150

20kg Grease Kit with Trolley \$1,495.00





### 8828N2

## **ALEMLUBE 20L ENGINE & GEAR OIL DRUM PUMP**

- Capable of delivering up to 110mL per stroke
- Downtube extension & extra Rieke adaptor make the pump suitable for use with a variety of 20L drums
- · Ideal pump for the transfer of engine, gear, diff & hydraulic oils
- · Drainback nozzle holster ensures that excess oil ends up back in the drum

\$74.00 GREAT VALUE!



#### 030060

## **EL SERIES** 205L MOBILE 3:1 OIL TRANSFER KIT WITH METER & TROLLEY

- Transfer kit flow rates of up to 10L/min
- Maximum operating pressure of 450psi (30bar)
- · High mobility kit complete with 3:1 ratio oil pump, 1/2" ID hydraulic hose, electronic oil meter, 2" bung adaptor to suit 205L drums & robust trolley \$1 **939**.00



## 454110N

## SAMOA

## 3:1 OIL TRANSFER KIT WITH METER

- 3:1 ratio pump, 3m x 1/2" ID hydraulic hose & electronic resettable meter
- Flow rates of up to 12L/min
- Air pressure range from 20psi to 140psi
- Air consumption 180NL/min (6.4 cfm)
- · Air inlet: 1/4" BSP(f)
- Fluid outlet: 1/2" BSP(f)

· Oil meter accurate to ± 0.5%



## ALEMLUBE **4 HOSE REEL GANTRY**

- Efficient mounting of 4 hose reels
- Durable powdercoat paint finish
- Ideal to install close to servicing bays
- Manufactured with high quality materials
- Conveniently store tools & general workshop equipment
- Dimensions: 2,500mm (H) x 1,290mm (W) x 600mm (D)



## AA205-3DG

GREAT VALUE!

## **ALEMLUBE AUTOMOTIVE 205L 3 DRUM LUBRICATION GANTRY**

- A cost-effective, low-maintenance oil delivery system
- Almlube 20m x 1/2" ID spring rewind oil hose reels
- · Digital metered control guns, with drip trays
- Heavy duty 5:1 oil drum pump
- 2"BSP drain port for bund included

## Also available:

AA205-2DG

2051 2 Drum Lubrication Gantry

\$6,640.00











# REWINDA HOSE REELS & DRUM PUMP

## AR1220CAB

### **REWINDA**

## **COMPRESSED AIR HOSE REEL - 20M X 12MM ID**

- Gen3 hybrid polymer hose
- 20m x 12mm ID hose & 0.9m lead-in hose
- 1/2" BSPT(m) inlet/outlet connections
- Maximum working pressure of 300 psi (20 bar)
- Working temperature of -40°C to +80°C
- High grade impact resistant UV stabilised covers
- Detachable steel mounting bracket enables 180° hose reel rotation
- Sliding guide system ensures that the hose returns neatly & evenly on to the barrel assembly

 Updated mounting brackets fit other leading brands

 Dimensions of 580mm (L) x 480mm (H) x 270mm (W)

# Also available: AR1220CAR

Compressed Air Hose Reel

- 20m x 12mm ID **\$449.00** 





## AR615OAR

## REWINDA

## OXY ACETYLENE HOSE REEL 15M X 6.3MM TWIN RUBBER ID HOSE

- Gen3 hybrid polymer hose
- High grade impact resistant UV stabilised covers for maximum durability
- Automatic & positive latching mechanism with speed control brake system
- Maximum working pressure of 300psi (20 bar)
- Two piece hose stop enables quick & easy hose length adjustment
- Can be mounted on the wall, ceiling, in utes & service vehicles
- Fully serviceable
- 15m x 6.3 mm twin Grade R rubber-ID hose & 0.9m lead-in

## Also available: AR615OPR

Oxy Propane Hose Reel 15m x 6.3mm Twin Rubber ID Hose **\$754.00** 

\$719.00 GREAT VALUE!



## 11028

## **ALEMLUBE**

## BATTERY OPERATED 20L OIL, ATF & COOLANT DRUM PUMP

If workshop productivity & profitability is a front of mind matter for you, the new Alemlube 11028 battery operated oil drum pump ought to be on your radar. With a delivery rate of up to 4.3L/min, a battery run time of up to 65 minutes, a battery recharge time of 45 minutes & a from full to empty battery delivery

of up to 280 litres effortless, fast and efficient oil transfer is available now. Whether your priority is saving energy for other more important tasks and functions in the workshop during business hours or for your pastimes after hours the Alemlube 11028 can deliver workshop efficiencies and an improved work/lifestyle balance for you and your team.

- Rugged, robust & dependable
- Transfers up to 280L per battery charge\*
- Flow rates of up to 4.3L/min\*
- · Battery run time of up to 65 minutes\*
- Battery recharge time of 45 minutes
- Carry handle assists with drum changeovers
- Interchangeable motor assembly
- 21.6V 2.5Ah Li-ion rechargeable battery
- 1.5m hose assembly and on/off nozzle
- Swivelling pump tube reduces the chance of annoying hose kinks

## Also available:

## 11028PTA

20L Oil, ATF & Coolant Drum Pump Tube Assembly



\*Figures as above based on 5W-30 engine oil

